



Color Variants

BOP250112
Full glass door in Gaggenau Metallic
Width 60 cm
BOP250102
Full glass door in Gaggenau Anthracite
Width 60 cm
BOP250132
Full glass door in Gaggenau Silver
Width 60 cm

Included accessories

1 x enamel baking tray.
suit. pyrolytic clean.
1 x glass pan.
1 x grill shelf.
1 x pluggable meat probe.

Optional accessories

BA016105
Pull-out system
BA026115
Baking tray, enamelled
BA036105
Wire rack, chromium-plated.
BA046117
Glass tray
BA056115
Heating element for baking stone and
Gastronorm roaster.
BA056133
Baking stone.
BA226105
Grill tray, enamelled
BS020002
Pizza paddle, set of 2.
GN340230
Gastronorm roaster in cast aluminium.

Product Variants

BOP251112
Oven 200 series
Full glass door in Gaggenau Metallic
Width 60 cm
Left-hinged

BOP250112
Oven 200 series
Full glass door in Gaggenau Metallic
Width 60 cm
Right-hinged



Flush installation
Pyrolytic system
13 heating methods with core temperature probe and baking stone function
Automatic programmes
Core temperature probe with estimation of cooking time
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 30 °C to 300 °C
Net volume 76 litres

Heating methods

Hot air.
Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting.

Handling

Rotary knob and TFT touch display operation.
Clear text display.
Option to save individual recipes (incl. core temperature probe).
Personalisation of automatic programmes.
Information key with use indicators.
Side-opening door opens up to 110° angle.

Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time.
Automatic programmes.
Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer (certified by Star-K).
60 W halogen light on the top.
Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.
Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.
The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Safety

Thermally insulated door with quintuple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.
The door panel surface of the appliance extends 21 mm from the furniture cavity.
The outer edge of the door handle extends 72 mm from the furniture cavity.
Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Characteristics
Gross weight
59.2
Color / Material Front
Built-in / Free-standing
Built-in
Integrated Cleaning system
Pyrolytic
Min. required niche size for installation (HxWxD)
590-590 x 560-560 x 550
Dimensions
595 x 590 x 547
Dimensions of the packed product (HxWxD)
760 x 710 x 650
Control Panel Material
without panel
Door Material
Glass
Net weight
55.0
Usable volume of cavity
76
Cooking method
Baking stone function, Bottom heat, Defrost setting, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top/bottom heat, Top heat
First cavity material
Number of interior lights
1
Length electrical supply cord
Interior Lights - cavity 1
1
Pull-out system
Accessory
Clock function
Alarm, Off, On, timer
Included accessories
1 x enamel baking tray,suit. pyrolytic clean, 1 x glass pan, 1 x grill shelf, 1 x pluggable meat probe
Bake Element Wattages cavity 1
Broil Element Wattages cavity 1
3000
Convection Element Wattages cavity 1
2100
Microwave wattage cavity 1
Drawer wattage
Energy efficiency rating
A
Energy consumption per cycle conventional - NEW (2010/30/EC)
1.25
Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)
Energy consumption per cycle forced air convection - NEW (2010/30/EC)
0.83
Energy consumption gas oven per cycle forced air convection - NEW (2010/30/EC)
Energy efficiency index (2010/30/EC)
95.4
Connection rating
3700
Fuse protection
16
Voltage
220-240
Frequency
50
Plug type
no plug
Connecting cable type
Universal Product Code
Color / Material Front
Alternative colors available
BOP250102, BOP250132
Energy input
Electric
Length of electrical supply cord (in)
Required cutout/niche size for installation (in)
x x
Dimensions of the packed product
29.92 x 25.59 x 27.95
Net weight
121.000
Gross weight
121.000

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 110° door opening angle.
For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
The mains socket needs to be planned outside the built-in niche.
The LAN port can be found at the back on the upper right side.

Connection
Energy efficiency class A at a range of energy efficiency classes from A+++ to D.
Total connected load 3.7 KW.
Plan a connection cable.
Plan a LAN cable.
Power consumption standby/display on 0.7 W.
Power consumption standby/display off 0.5 W.
Power consumption standby/network 1.4 W.
Time auto-standby/display on 20 min.
Time auto-standby/display off 20 min.
Time auto-standby/network 20 min.
Please check the user manual for how to switch off the WiFi module.



